

# PEAK

ORIGINAL EQUIPMENT TECHNOLOGY

**dexcool™**  
GM APPROVED

**ANTIFREEZE + COOLANT**

## DESCRIPTION

**PEAK® ORIGINAL EQUIPMENT TECHNOLOGY™ DEX-COOL® ANTIFREEZE + COOLANT** is a premium GM-approved extended life coolant engineered to match technology and color requirements for all vehicles model years 1995 and newer. This coolant is formulated with the same corrosion inhibitor technology that protected your vehicle straight from the factory. Color cues on the packaging and a list of covered vehicles on the front label make it easy to confirm that this is the right match for your specific GM vehicle.

**PEAK® Original Equipment Technology™ DEX-COOL® Antifreeze + Coolant** utilizes a carefully balanced mixture of Organic Acid Technology (OAT) corrosion inhibitors for complete protection of modern high-performance GM vehicle engines. It is free of silicate, borate, phosphate, nitrite and amines, and is fully compatible with other extended life coolants. It can be mixed with any DEX-COOL® approved formulation and its distinctive orange color matches that of the original factory fill coolant.

**PEAK® Original Equipment Technology™ DEX-COOL® Antifreeze + Coolant** meets the performance requirements of ASTM D3306 and D4985. When installed as part of a complete cooling system flush and fill, PEAK guarantees this coolant will provide service life protection of up to 5 years or 150,000 miles<sup>1</sup>.

## FEATURES & BENEFITS

- Matches technology and color requirements of GM vehicles specifying a DEX-COOL® coolant
- Protects all cooling system metals, including aluminum, against damaging rust and corrosion
- Meets the performance requirements of ASTM D3306, D4985 and GMW3420, GM6277M
- Compatible with other orange OAT formulations
- Color-coding and vehicle applications listed on the front simplify selecting the right antifreeze/coolant

Use PEAK ORIGINAL EQUIPMENT TECHNOLOGY ANTIFREEZE + COOLANT concentrate to perform a complete flush/fill or top-off.

Use PEAK ORIGINAL EQUIPMENT TECHNOLOGY 50/50 PREDILUTED ANTIFREEZE + COOLANT when just topping off your system.



For more information on cooling system maintenance including how-to videos, visit [peakauto.com/diy-hub](http://peakauto.com/diy-hub).

<sup>1</sup>See warranty details at [www.PEAKguarantee.com](http://www.PEAKguarantee.com)

# A PERFECT MATCH FOR EVERY VEHICLE



## PROTECTION CHART

Coolant/Water Ratio	PROTECTS FROM	
	Freezing Down to	Boiling Up to**
50/50	-34°F (-36°C)	265°F (129°C)
60/40	-62°F (-52°C)	270°F (132°C)
70/30	-84°F (-64°C)	276°F (135°C)

\*\*Using a 15 psig (103 kPa) pressure cap



Available in both 50/50 Prediluted and Concentrate

08-08-2022



# ORIGINAL EQUIPMENT TECHNOLOGY™ ANTIFREEZE + COOLANT

## APPLICATIONS

**PEAK® Original Equipment Technology™ DEX-COOL® Antifreeze + Coolant** is specifically engineered for use in all GM vehicles requiring DEX-COOL® ORANGE OAT extended life antifreeze/coolant:

- GM: cars, SUVs, light and medium duty trucks 1995 and newer

PROPERTIES	ASTM TEST METHOD	TYPICAL VALUES		ASTM D3306 Limits
		CONCENTRATE	PREDILUTED (50/50)	
Appearance	Visual	Orange	Orange	Distinctive
pH, (50% vol)	D1287	8.3	8.3	7.5-11.0
Specific gravity	D1122	1.122	1.066	1.110-1.145 <sup>1</sup> / 1.065 min <sup>2</sup>
Boiling point <sup>3</sup> , °C (°F)	D1120	162.8 (325)	109.5 (229.1)	108 (226) Min
Freezing point, °C (°F)	D1177		-38.8 (-37.8)	-36.4 (-34) Max
Effect on Automotive Finish	D1882	No Effect	No Effect	No Effect
Total water, mass %	D1123	<5	50	5 Max <sup>1</sup>
Ash content, mass %	D1119	<5	<2.5	5 Max <sup>1</sup> / 2.5 Max <sup>2</sup>
Chloride, ppm	D3634	<25	<25	25 Max

<sup>1</sup>For concentrate product only, <sup>2</sup>Prediluted (50/50) only, <sup>3</sup>Unpressurized

## SHIPPING INFORMATION



### CONCENTRATE

NAD0B3

1 Gallon Bottle

0-74804-07109-2

6/1 Gallon Case

0-74804-17109-9



### 50-50 PREDILUTED

NADB53

1 Gallon Bottle

0-74804-07110-8

6/1 Gallon Case

0-74804-17110-5

Part #	Unit	Pack/Size	Dimensions	Unit Wt. (lbs.)	Units per Pallet	Pallets per Truck	Pallet Weight**
NAD0B3	Case	6/1 gal	16" L x 12.5" W x 12.25" H	60	36	20	2,210
NADB53	Case	6/1 gal	16" L x 12.5" W x 12.25" H	57	36	20	2,102

\*\*Includes pallet weight of 50 lbs each

## ADDITIONAL INFORMATION

**Testing Requirements:** For proper freeze and boilover protection, use a traditional refractometer or hydrometer to measure the percentage of ethylene glycol by volume.

**Storage Recommendations:** PEAK Original Equipment Technology DEX-COOL® Antifreeze + Coolant can be stored in original container at ambient temperature with limited periods of exposure to temperatures above 95°F (35°C) for 3-5 years, provided the container remains sealed. Product should be agitated before dilution or use.

**Safety and Environmental Guidance:** PEAK Original Equipment Technology DEX-COOL® Antifreeze + Coolant contains virgin ethylene glycol and should be kept away from children and animals to prevent exposure. A bittering agent is added to help reduce the potential for accidental ingestions of this product. More information with guidance on health, safety and disposal is available on the appropriate Safety Data Sheet, which can be obtained from [peakauto.com](http://peakauto.com). Always dispose of used coolant in accordance with local, state and Federal guidelines.

DEX-COOL® Concentrate SDS ID: 115014

DEX-COOL® 50/50 Prediluted SDS ID: 115013

Old World Industries, LLC.  
Northbrook, IL 60062 • 800-323-5440  
[Peakauto.com](http://Peakauto.com)



To order, please call  
Old World Industries Customer Service at  
**1-800-323-8755**

Manufactured for Old World Industries, Northbrook, IL 60062 • (800) 289-7234  
MADE IN THE USA OF DOMESTIC AND FOREIGN CONTENT  
©2022 Old World Industries. All Rights Reserved.  
PEAK, PEAK & Mountain Graphic and PEAK ORIGINAL EQUIPMENT TECHNOLOGY & Graphic  
and ORIGINAL EQUIPMENT TECHNOLOGY are trademarks of Old World Industries.  
GM and DEX-COOL are registered trademarks of General Motors LLC.  
DEX-COOL license number: DC-21-7

08-08-2022